

<html>  
<body>

What is the function of the ucfirst and lcfirst functions?  
-To make the string's first character uppercase or lowercase, respectively  
What will the following script output?-\$array=array  
-78

comment

Script use in every php code. (Note : No spaces needed)

<?php?>

PHP is now known as "PHP: Hypertexts Preprocessor"

false

Define styles for your documents, including the design, layout and variations in display for different devices and screen sizes.

CSS

Identification. Write your answer on the space provided. PHP version that uses void return type, class constant visibility modifiers, null types

php 7.1

Symbol used to combine 2 sting values to create one string.

.

Symbol use to append data or string

.=

PHP is proprietary software.

false

PHP 3 was released in 1998.

true

What does PHP stand for?

PHP: Hypertext Preprocessor

PHP variables need to be declared before adding a value to it?

false

PHP can be run on Microsoft Windows IIS(Internet Information Server):

false

Which one of these variables has an illegal name?

\$my-Var

It is a function that removes an existing file from the server.

unlink

PHP development began in 1995.

false

All text in a multiple line comment block is ignored?

true

Inventor of PHP

text input control.

Function is used to display structured information (type and value) about one or more variables.

var\_dump()

All text to the right of a single line comment is not ignored?

false

For maximum compatibility, you should use the shorthand form to create PHP scripts?

false

Version of PHP what uses namespace support late static binding

5.3

Syntax is a set of rules that must be followed to write properly structured code?

true

How do you start the standard form PHP scripting block?

<?php ?>

Which of the following is the incorrect way to declare a PHP variable?

\$a Variable;

If a source file contains PHP code, what extension should be used?

.php

Multiple Choice. Select the best answer

In PHP you can use both single quotes ( ' ' ) and double quotes ( " " ) for strings:

/ \*...\* /

php.org is the official php resource.

false

When a variable is declared, it can only be used 1 time in your PHP source file?

false

Identification. Write your answer on the space provided.

This are used with numeric values to perform common arithmetical operations, such as addition, subtraction, multiplication etc

arithmetic operators

Identification. Write your answer on the space provided.

Which operator will check if two variables are the same?

comparison operator

( (2 >= 2 && 8 < 1) || (11 == 33 || 5 > 3) )

true

True or False - The operator OR, when used to link two or concept terms will retrieve fewer records because both terms need not be present in each article.

false

Identification. Write your answer on the space provided.

+, -, \*, /, %, are all examples of what category of operators

arithmetic operator

The following condition will return TRUE or FALSE: (7 >= 7 && 9 < 2)

false

Which of the following that can be use to access session variables in PHP?

\$\_SESSION

It is an array containing information such as headers, paths and script locations wherein it is created by the web server itself

\$\_SERVER

Sorts by value in reverse order; keeps the same key

arsort()

This function is used to close the current session.

session\_destroy()

Generate fatal error.

define

It is a SQL keyword that creates an autoincrementing field.

AUTO\_INCREMENT

It opens a connection to a MySQL database server

mysql\_connect / mysqli\_connect

It is a function that saves the uploaded file permanently into the server.

move\_uploaded\_file()

It is a file function mode that is used to open a file for reading, writing or appending.

fopen

Allow for multiple items of the same type to be aggregated under a single representative entity.

Compound Datatypes

It specifies the name of the field in the form to be processed by the \$\_FILES file

It is used to access submitted form values

\$\_POST

It is an attribute that must be used in the form tag in specifying an input file type

enctype

It is placed within the code of a loop to cause the program to stop the loop statement.

break

It proceeds the statement causes execution of the current loop iteration to end and commence at the beginning of the next loop.

continue

It is a function that retrieves the content of one cell from a MySQL result set.

mysql\_fetch\_row()

mysqli\_fetch\_row()

Format character of Date function that display the day of the month in 2 digits with leading zeros such as 01 to 31

d

Assume you would like to sort an array in ascending order by value while preserving key associations. Which of the following PHP sorting functions would you use?

asort()

Array values are keyed by \_\_\_\_\_ values (called indexed arrays) or using \_\_\_\_\_ values (called associative arrays). Of course, these key methods can be combined as well.

integer, string

Generate fatal error.

iInclude\_once()

It is a function that retrieves the number of rows from a query result set.

mysql\_affected\_rows()

mysqli\_affected\_rows()

Format character of Date function that display a full textual representation of the day of the week such as Sunday to Saturday

d

Which of the following that can be use read cookies in PHP?

setcookie()

This function removes the white spaces and other predefined characters from both sides of a string

trim

Join array elements to form a string.

implode

Managing of cookies can be done using this function

cookie()

</body>

</html>